

Data sheet

Laboratory Incubator CLN 180



The photo above is for reference only, may show additional options not included in standard equipment.
The real appearance, particularly color and structure of the material may differ from the ones presented in the photo.

TECHNICAL DATA

air convection	natural
chamber capacity [l] /1/	180
working capacity [l]	180
controller	microprocessor with external LCD graphic display

TEMPERATURE

temperature range [°C]	+5°C above ambient temperature ... +100°C
temperature resolution every ... [°C]	0,1
over temperature protection	class 2.0 to DIN 12880 / class 3.1 (option) / class 3.1 in TOP+

CHAMBER

door type	double / door with viewing window (option)
-----------	--

interior

STD	acid-proof stainless steel to DIN 1.4301
INOX/G	acid-proof stainless steel to DIN 1.4301

housing


STD	powder coated sheet
INOX/G	stainless steel linen finish

overall dims [mm] /2/

width A	650
height B	1030
depth C	760

internal dims [mm]

width D	470
height E	720
depth F	560



shelves (standard / max)	3 / 9
max shelf workload [kg] /5/	25
- reinforced shelf version (PW) /3/	50
max unit workload [kg]	75
- reinforced unit version (W) /4/	120
weight [kg]	94

ELECTRICAL PARAMETERS

voltage*	230V 50Hz
nominal power [W]	850
warranty	24 months
manufacturer	POL-EKO-APARATURA

all the above technical data refer to standard units (without optional accessories)

- * - 230V 60Hz, 115V 60Hz also available
- 1 - working capacity of chamber can be smaller
- 2 - depth doesn't include 50 mm of power cable
- 3 - reinforced shelf
- 4 - reinforced version
- 5 - on uniformly loaded surface

OPTIONS AND ACCESSORIES

