

TRIO.BAS DUO cable

TRIO.BAS™

ORUM INTERNATIONAL
© ALL RIGHTS RESERVED



Two aspirating heads air sampler with Bluetooth
and cable for charging



- 100 or 200 litres per minute flow rate model
- Bluetooth for data transfer
- Cable for battery charger
- Cable for data transfer
- Stable on a work surface in a vertical position without the use of any external support
- Stainless steel AISI 316 aspirating head with quick bayonet closure and identification number
- Suitable for 55 mm Contact plates or 90 mm Petri dishes
- Up to 1.000 memorized data, 100 places identification, 100 operators identification
- More than one different culture media at the same time
- Saved sampling time by doubling the aspirated volume of air

DESCRIPTION

- This air sampler is especially dedicated to customers who make a large number of controls, in different environments, with a large staff rotation and comply with the quality standards and QM/GMP.
- Main customers are pharmaceutical aseptic filling suites, cleanroom, biotech, IVF clinic, operating theatre, hospital pharmacies, blood banks, clinic, microbiological labs, HVAC building monitoring, environmental labs, healthcare ambient monitoring and health authorities.
- A barcode module, thanks to the use of a scanner (barcode reader) with Bluetooth, automatically records the operator, place and plates used for the sampling. The data collected by the barcode reader are transmitted directly to the instrument. This solution is useful for those who already use culture plates with barcode or 2-D barcode (QR Quick Response Code). The data collected are transferred via Bluetooth from the air sampler to a PC or laptop. PC or laptop request a dedicated software (ASPC) installed.
- The data are transferred via Bluetooth between the air sampler and a smartphone or tablet (Android version) and then to a PC or laptop.
- The data may be transferred via cable, too. This is helpful for all companies that, due to internal policy, are not allowed to use the wireless transfer.
- It is possible to work either in manual or automatic mode.
- The sampler is IP65 certified.
- The battery is recharged by a power cable connected directly to the air sampler.
- While under charging, the air sampler can sample.
- The 200 lts/min air flow reduces the operator time and the time sampling.
- The use of sterile Daily Shift aspirating heads reduces the risk of contamination.
- The possibility to use 2 different aspirating heads allows to have 2 different culture media at the same time or to make sampling BEFORE (at rest), DURING (in operation) and at the END of each processing cycle.

PERFORMANCES

- Light weight, ergonomic and balanced design to facilitate handling with or without gloved hands
- Technopolymer body shockproof with antibacterial performances of surfaces
- Complaint according EN/ISO 14968-1, GMP and GLP
- Stainless steel aspirating head with quick bayonet closure, identification number and stainless steel cover to prevent contamination
- Volume of aspirating air: 100 or 200 l/m
- Selected volumes from 30 to 2.000 l/m and 17 preset programs
- The aspirating chamber is suitable for 55 mm Contact plates or 90 mm Petri dishes
- Auto calibration: power/flow electronic real time control
- Power supply system: the instrument can be charged continuously by AC powered source 110/240 Volt 50/60 Hz or by rechargeable batteries (inserted inside the air sampler)
- Cycles battery autonomy: 70.000 litres
- IP65 protection certificate from dust and water
- Language: English, French, German, Spanish, Italian
- Manual and automatic passwords
- Operative aspirating cycles: manual and automatic
- Memorized data: up to 1.000 samplings
- Configuration users and places: 100
- Delayed, remote, start, simultaneous or interval sampling
- Bluetooth connection or cable for data transfer
- Automatic next calibration reminder
- Programmable for compressed gases/air
- Data integrity CFR 21
- CE mark
- Continuous/trending analysis according USP
- Dimension: 26x28x15h cm
- Weight: 1.630 gr
- Built in ISO 9000 premises


IDENTIFICATION CODES

Code	TRIO.BAS DUO cable PACK (*)
222K	TRIO.BAS DUO 100 Contact PACK with cable (100 litres/min flow rate)
223K	TRIO.BAS DUO 100 Petri PACK with cable (100 litres/min flow rate)
231K	TRIO.BAS DUO 200 Contact PACK with cable (200 litres/min flow rate)
232K	TRIO.BAS DUO 200 Petri PACK with cable (200 litres/min flow rate)

(*) each PACK consists of: 1 TRIO.BAS DUO with battery charger, 1 calibration certificate, 2 s/s ASPI head with s/s cover head, 1 cable for transfer data, 1 robustus carrying case.



TRIO.BAS DUO with cable



Stainless steel aspirating head with quick bayonet closure



Stable on a work surface in a vertical position