

INWO

-

OmniGLH general lab homogenizer

The **Omni GLH**, General Laboratory Homogenizer is a powerful, durable and versatile homogenizer that can handle virtually any processing application. Its 700 watt heavy motor is designed to completely disrupt even the move difficult samples, quickly and efficiently, with repeatable results-every time.

The **Omni GLH** processes samples ranging from 200 μ L to 10 liters, and is compatible with a wide range of accessories, including:

• Stainless steel generator probes in a variety of sizes (5 mm through 35mm diameter probes). Omni generator probes are constructed of 316L stainless steel, are durable and easy to disassemble for cleaning.

• Patented **Omni Tip[™] Plastic Generator Probes**, (hard and soft tissue versions) which eliminate cross contamination, sample loss and carryover concerns between samples.

• Hybrid 2 piece stainless steel and plastic probes.

The **Omni GLH is equipped with an internal variable speed controller**. An optional **External Speed Control** is available, enabling greater precision or remote operation beneath a fume hood.

Applications for use:

- > Petroleum by-products & waste
- > QA/QC tablets and capsules
- > Lotions & oil emulsions, suspensions
- > Culinary use featured in Modernist Cuisine
- > Paper pulp processing

- > Paint, ink and dye application
- > Food testing (QUEChERs, QA/QC)
- > Bulk vaccine products
- > RNA, DNA extraction from tissues
- > Environmental testing



Omni GLH shown with optional motor stand assembly and stainless steel probe.

ORDER NO. GLH-115 STAND: ORDER NO. \$1000

Omni GLH

General Lab Homogenizer Accessories

The versatile **Omni GLH Line** offers a wide variety of accessories for all of your processing needs.



Vessel Restraint Disk can be used to help reduce splashing and contain aerosols during homgenization.

ORDER NO. LT-750



ORDER NO. S1000









Generator probes from 5 mm to 35 mm



- > Powerful 700 watt motor
- Variable motor speeds from 5,000 to 28,000 rpm
- > Processing range from <200 μ L to 10 L

> Specifications

Processing Range: <200 µL to 10 L

Speed: Variable from 5,000 to 28,000 rpm

Power Rating: 700 watt max

Dimensions:

8.5" H (22 cm) x 2.75" (7 cm) diameter





External Speed Control is available for remote operation beneath a fume hood.

ORDER NO. SC115

Omni Tip[™] Plastic Homogenizer Probes generator probes completely eliminate cross-contamination and cleaning between samples ORDER NO. 30750 (25 pack)

> For more information — **Omni-inc.com**

Omni International, Inc. 935C Cobb Place Blvd. Kennesaw, GA 30144 800.776.4431 • 770.421.0058

